



TBR TIRE

Long Haul	47
Regional	55
Mixed Service	69
Logging	73
Coach&Bus	74
Winter	75

CONTENTS



LongHaul

LEAO TIRE

NEW



KTD10

Radial Truck Tire(Long Haul)

- 1.Suitable for the drive axle of the trucks running on highway
- 2.Low rolling resistance reduces fuel consumption
- 3.Closed shoulder to fight irregular wear
- 4.New pattern design improves mileage for long-distance transportation

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
11R22.5	144/142L	14	G	8.25	5840	105	6175	105	41.93	10.98	495	30.0
11R22.5	146/143L	16	H	8.25	6005	120	6610	120	41.93	10.98	495	30.0
11R24.5	146/143L	14	G	8.25	6005	105	6610	105	43.94	10.98	473	30.0
11R24.5	149/146L	16	H	8.25	6610	120	7160	120	43.94	10.98	473	30.0
285/75R24.5	144/141L	14	G	8.25	5675	110	6175	110	41.81	11.14	497	28.0
285/75R24.5	147/144L	16	H	8.25	6175	120	6780	120	41.81	11.14	497	28.0
295/75R22.5	144/141L	14	G	9.00	5675	110	6175	110	40.39	11.73	514	28.0
295/75R22.5	146/143L	16	H	9.00	6005	120	6610	120	40.39	11.73	514	28.0



AFE891

Radial Truck Tire(Long Haul)

- 1.Recommended for on-high Long haul steer applications.
- 2.Intermediate defense rib to control irregular wear.
- 3.Tread design optimized for reduced stone retention.
- 4.Construction optimized for fuel economy and long tread life.

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
295/75R22.5	144/141L	14	G	9.00	5675	110	6175	110	39.92	11.73	520	20.8
295/75R22.5	146/143L	16	H	9.00	6005	120	6610	120	39.92	11.73	520	20.8

Remark : The above technical data are for reference only.



NEW

ADE892

Radial Truck Tire(Long Haul)

- 1.Recommended for on-high Long haul drive applications.
- 2.Tread design helps deliver all-season traction and reduction of uneven wear.
- 3.Construction optimized for fuel economy and long tread life.

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
11R22.5	144/142L	14	G	8.25	5840	105	6175	105	41.93	10.98	495	27.7
11R22.5	146/143L	16	H	8.25	6005	120	6610	120	41.93	10.98	495	27.7
11R24.5	146/143L	14	G	8.25	6005	105	6610	105	43.94	10.98	473	27.7
11R24.5	149/146L	16	H	8.25	6610	120	7160	120	43.94	10.98	473	27.7
285/75R24.5	144/141L	14	G	8.25	5675	110	6175	110	41.81	11.14	497	27.7
285/75R24.5	147/144L	16	H	8.25	6175	120	6780	120	41.81	11.14	497	27.7
295/75R22.5	144/141L	14	G	9.00	5675	110	6175	110	40.39	11.73	514	27.7
295/75R22.5	146/143L	16	H	9.00	6005	120	6610	120	40.39	11.73	514	27.7

Remark : The above technical data are for reference only.



LLF16

Radial Truck Tire (Long Haul)

- 1.Recommended for long haul applications.
- 2.Decoupling groove in shoulder to control irregular wear.
- 3.Construction optimized for long tread life.

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
11R22.5	144/142M	14	G	8.25	5840	105	6175	105	41.50	10.98	501	18.3
11R22.5	146/143M	16	H	8.25	6005	120	6610	120	41.50	10.98	501	18.3
11R24.5	146/143M	14	G	8.25	6005	105	6610	105	43.46	10.98	478	18.3
11R24.5	149/146M	16	H	8.25	6610	120	7160	120	43.46	10.98	478	18.3
285/75R24.5	144/141M	14	G	8.25	5675	110	6175	110	41.34	11.14	503	18.3
285/75R24.5	147/144M	16	H	8.25	6175	120	6780	120	41.34	11.14	503	18.3
295/75R22.5	144/141M	14	G	9.00	5675	110	6175	110	39.92	11.73	520	18.3
295/75R22.5	146/143M	16	H	9.00	6005	120	6610	120	39.92	11.73	520	18.3

Remark : The above technical data are for reference only.



SMARTWAY

LLF16e+

Radial Truck Tire (Long Haul)

- 1.Recommended for long haul applications.
- 2.Decoupling groove in shoulder to control irregular wear.
- 3.Construction optimized for fuel economy and long tread life.

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
11R22.5	144/142M	14	G	8.25	5840	105	6175	105	41.50	10.98	501	18.3
11R22.5	146/143M	16	H	8.25	6005	120	6610	120	41.50	10.98	501	18.3
11R24.5	146/143M	14	G	8.25	6005	105	6610	105	43.46	10.98	478	18.3
11R24.5	149/146M	16	H	8.25	6610	120	7160	120	43.46	10.98	478	18.3
285/75R24.5	144/141M	14	G	8.25	5675	110	6175	110	41.34	11.14	503	18.3
285/75R24.5	147/144M	16	H	8.25	6175	120	6780	120	41.34	11.14	503	18.3
295/75R22.5	144/141M	14	G	9.00	5675	110	6175	110	39.92	11.73	520	18.3
295/75R22.5	146/143M	16	H	9.00	6005	120	6610	120	39.92	11.73	520	18.3

Remark : The above technical data are for reference only.



LLD37

Radial Truck Tire (Long Haul)

1. Recommended for on-highway Long Haul and Regional drive applications.
2. Shoulder and center block design provides traction in all conditions.
3. Construction optimized for long service life.

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
11R22.5	144/142M	14	G	8.25	5840	105	6175	105	41.93	10.98	495	27.7
11R22.5	146/143M	16	H	8.25	6005	120	6610	120	41.93	10.98	495	27.7
11R24.5	146/143M	14	G	8.25	6005	105	6610	105	43.94	10.98	473	27.7
11R24.5	149/146M	16	H	8.25	6610	120	7160	120	43.94	10.98	473	27.7
285/75R24.5	144/141M	14	G	8.25	5675	110	6175	110	41.81	11.14	497	27.7
285/75R24.5	147/144M	16	H	8.25	6175	120	6780	120	41.81	11.14	497	27.7
295/75R22.5	144/141M	14	G	9.00	5675	110	6175	110	40.39	11.73	514	27.7
295/75R22.5	146/143M	16	H	9.00	6005	120	6610	120	40.39	11.73	514	27.7



SMARTWAY

ADL817

Radial Truck Tire (Long Haul)

1. Recommended for on-highway long haul and regional drive applications.
- 2.Tread design helps deliver all-season traction and reduction of uneven wear.
3. Reduces weight for increased payload (vs duals).
4. Construction optimized for fuel economy and long tread life.

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
445/50R22.5	161L	20	L	14.00	/	/	10200	120	40.31	17.52	519	25.2

Remark : The above technical data are for reference only.



SMARTWAY

ATE821

Radial Truck Tire(Long Haul)

1. Recommended for on-highway trailer applications.
2. Decoupling groove in shoulder to control irregular wear.
3. Wide footprint for long mileage.
4. Low rolling resistant to save fuel costs.

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
11R22.5	144/142M	14	G	8.25	5840	105	6175	105	41.50	10.98	501	12.0
11R22.5	146/143M	16	H	8.25	6005	120	6610	120	41.50	10.98	501	12.0
11R24.5	146/143M	14	G	8.25	6005	105	6610	105	43.46	10.98	478	12.0
11R24.5	149/146M	16	H	8.25	6610	120	7160	120	43.46	10.98	478	12.0
285/75R24.5	144/141M	14	G	8.25	5675	110	6175	110	41.34	11.14	503	12.0
285/75R24.5	147/144M	16	H	8.25	6175	120	6780	120	41.34	11.14	503	12.0
295/75R22.5	144/141M	14	G	9.00	5675	110	6175	110	39.92	11.73	520	12.6
295/75R22.5	146/143M	16	H	9.00	6005	120	6610	120	39.92	11.73	520	12.6

Remark : The above technical data are for reference only.



SMARTWAY

LLD37e+

Radial Truck Tire (Long Haul)

1. Recommended for on-highway Long Haul and Regional drive applications
2. Shoulder and center block design provides traction in all conditions
3. Low rolling resistant to save fuel costs.

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
11R22.5	144/142M	14	G	8.25	5840	105	6175	105	41.93	10.98	495	22.0
11R22.5	146/143M	16	H	8.25	6005	120	6610	120	41.93	10.98	495	22.0
11R24.5	146/143M	14	G	8.25	6005	105	6610	105	43.94	10.98	473	27.7
11R24.5	149/146M	16	H	8.25	6610	120	7160	120	43.94	10.98	473	27.7
285/75R24.5	144/141M	14	G	8.25	5675	110	6175	110	41.81	11.14	497	27.7
285/75R24.5	147/144M	16	H	8.25	6175	120	6780	120	41.81	11.14	497	27.7
295/75R22.5	144/141M	14	G	9.00	5675	110	6175	110	40.39	11.73	514	27.7
295/75R22.5	146/143M	16	H	9.00	6005	120	6610	120	40.39	11.73	514	27.7



SMARTWAY

ATL811

Radial Truck Tire (Long Haul)

1. Recommended for on-highway trailer applications.
2. Reduces weight for increased payload (vs duals).
3. Construction optimized for fuel economy and long tread life.

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
445/50R22.5	161L	20	L	14.00	/	/	10200	120	40.09	17.52	522	13.2

Remark : The above technical data are for reference only.



Regional

LEAO TIRE

NEW

SMARTWAY



KTA20

Radial Truck Tire(Regional)

1. Suitable for all position of trucks using for high traction and high scrub applications.
2. Wide, strong shoulder ribs increase tread life.
3. Lasting grip and stability.
4. High wear resistance.

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
11R22.5	144/142L	14	G	8.25	5840	105	6175	105	41.50	10.98	501	19.0
11R22.5	146/143L	16	H	8.25	6005	120	6610	120	41.50	10.98	501	19.0
11R24.5	146/143L	14	G	8.25	6005	105	6610	105	43.46	10.98	478	19.0
11R24.5	149/146L	16	H	8.25	6610	120	7160	120	43.46	10.98	478	19.0
285/75R24.5	144/141L	14	G	8.25	5675	110	6175	110	41.34	11.14	503	19.0
285/75R24.5	147/144L	16	H	8.25	6175	120	6780	120	41.34	11.14	503	19.0
295/75R22.5	144/141L	14	G	9.00	5675	110	6175	110	39.92	11.73	520	19.0
295/75R22.5	146/143L	16	H	9.00	6005	120	6610	120	39.92	11.73	520	19.0



NEW

KTD23

Radial Truck Tire(Regional)

1. Suitable for drive axle of trucks using for high traction and high scrub applications.
2. Aggressive pattern provides tire excellent drive and braking performance.
3. Shoulder pattern groove and open pattern design with good tire heat dissipation.

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
215/75R17.5	135/133L	16	H	6.00	4540	123	4805	123	30.20	8.35	688	18.9
225/70R19.5	125/123L	12	F	6.75	3415	95	3640	95	31.93	8.90	651	19.9
225/70R19.5	128/126L	14	G	6.75	3750	110	3970	110	31.93	8.90	651	19.9
245/70R19.5	133/131L	14	G	7.50	4300	110	4540	110	33.03	9.76	629	19.9
245/70R19.5	135/133L	16	H	7.50	4540	120	4805	120	33.03	9.76	629	19.9

Remark : The above technical data are for reference only.



LLA78

Radial Truck Tire(Regional)

- 1.Recommended for low platform trailer applications
- 2.Zig-zag groove tread design reduces stone retention

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
235/75R17.5	143/141J	18	J	6.75	5675	127	6005	127	31.38	9.17	662	16.4



AFL866

Radial Truck Tire(Regional)

- 1.Recommended for low platform trailer applications.
- 2.Construction optimized for long service life.

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
215/75R17.5	135/133J	16	H	6.00	4540	123	4805	123	30.20	8.35	688	18.3
235/75R17.5	143/141J	18	J	6.75	5675	127	6005	127	31.38	9.17	662	18.3
245/70R17.5	143/141J	18	J	7.50	5675	127	6005	127	31.06	9.76	669	18.3



F820

Radial Truck Tire(Regional)

Recommended for Regional and Pick Up/Deliver application.

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
215/75R17.5*	135/133J	16	H	6.00	4540	123	4805	123	30.20	8.35	688	15.7
235/75R17.5*	143/141J	18	J	6.75	5675	127	6005	127	31.38	9.17	662	16.4
225/70R19.5	125/123M	12	F	6.75	3415	95	3640	95	31.93	8.90	651	15.7
225/70R19.5	128/126M	14	G	6.75	3750	110	3970	110	31.93	8.90	651	15.7
245/70R19.5	133/131M	14	G	7.50	4300	110	4540	110	33.03	9.76	629	16.4
245/70R19.5	135/133M	16	H	7.50	4540	120	4805	120	33.03	9.76	629	16.4
265/70R19.5	140/138M	16	H	7.50	5205	112	5510	112	34.13	10.31	609	17.0
285/70R19.5	150/147J	18	J	8.25	6780	130	7390	130	35.24	11.14	590	17.6
255/70R22.5	140/137M	16	H	7.50	5070	120	5510	120	36.61	10.04	567	17.6
275/70R22.5	148/145M	16	H	8.25	6395	130	6945	130	37.72	10.87	551	18.3

*Recommended for low platform trailer application



LLF86

Radial Truck Tire (Regional)

Recommended for low platform trailers

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
215/75R17.5	135/133J	16	H	6.00	4540	123	4805	123	30.20	8.35	688	15.7

Remark : The above technical data are for reference only.

Remark : The above technical data are for reference only.



LLF56+

Radial Truck Tire (Regional)

1. Recommended for light and medium duty Regional and Pick Up/Delivery applications.
2. Solid shoulder provides for long, even wear.

Size	Load Index & Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
9R22.5	136/134M	14	G	6.75	4675	120	4940	120	38.35	9.02	542	17.0
10R22.5	141/139M	14	G	7.50	5355	115	5675	115	40.16	10.00	518	17.6



F835

Light Truck Tire (Regional)

1. Recommended for Light Truck applications.
2. Variable angled tread pattern reduces stone retention.
3. Tread pattern delivers lateral traction in all weather conditions.

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
LT225/75R16	119/116N	12	F	6.00	2755	95	3000	95	29.29	8.78	708	14.0
LT235/85R16	126/123L	14	G	6.50	3415	110	3750	110	31.73	9.25	655	11.2
LT245/75R16	123/120N	12	F	7.00	3085	95	3415	95	30.47	9.76	681	14.0



LLF02

Radial Truck Tire (Regional)

1. Designed for on-highway heavy load applications.
2. Wide footprint for even weight distribution.

Size	Load Index & Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
12R22.5	152/149L	18	J	9.00	7160	135	7825	135	42.68	11.81	487	18.3
295/80R22.5	152/149M	18	J	9.00	7160	130	7830	130	41.10	11.73	505	18.3
315/80R22.5	154/151M	18	J	9.00	7610	120	8270	120	42.36	12.28	490	18.3
315/80R22.5	157/154L	20	L	9.00	8270	130	9090	130	42.36	12.28	490	18.3



ADL831

Radial Truck Tire (Regional)

1. Recommended for light and medium duty Regional and Pick Up/Delivery drive applications.
2. Rigid block design provides traction in all conditions.
3. Construction optimized for long service life.

Size	Load Index & Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
215/75R17.5	135/133J	16	H	6.00	4540	123	4805	123	30.20	8.35	688	20.2
235/75R17.5	143/141J	18	J	6.75	5675	127	6005	127	31.38	9.17	662	21.4
245/70R17.5	143/141J	18	J	7.50	5675	127	6005	127	31.06	9.76	669	22.7

Remark : The above technical data are for reference only.

Remark : The above technical data are for reference only.

SMARTWAY



LLA08e+

Radial Truck Tire (Regional)

1. Recommended for regional applications.
2. Variable angled tread pattern reduces stone retention.
3. Tread pattern delivers lateral traction in all weather conditions.

Size	Load Index & Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
11R22.5	146/143K	16	H	8.25	6005	120	6610	120	41.50	10.98	501	18.9
11R24.5	149/146K	16	H	8.25	6610	120	7160	120	43.46	10.98	478	20.8



D955

Radial Truck Tire (Regional)

1. Recommended for Regional and Pickup/Delivery drive applications.
2. Tread pattern provides traction in all weather conditions.

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
225/70R19.5	128/126M	14	G	6.75	3750	110	3970	110	31.93	8.90	651	18.3
245/70R19.5	135/133L	16	H	7.50	4540	120	4805	120	33.03	9.76	629	19.5



D905

Radial Truck Tire (Regional)

1. Recommended for on-highway Regional and Pickup/Delivery drive applications.
2. Wide circumferential grooves reduce hydroplaning.
3. Open Shoulder tread pattern delivers traction in all weather conditions.

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
215/75R17.5	135/133L	16	H	6.00	4540	123	4805	123	30.20	8.35	688	18.9
235/75R17.5	143/141J	18	J	6.75	5675	127	6005	127	31.38	9.17	662	19.5
245/70R17.5	143/141J	18	J	7.50	5675	127	6005	127	31.06	9.76	629	22.7
225/70R19.5	125/123M	12	F	6.75	3415	95	3640	95	31.93	8.90	651	18.9
225/70R19.5	128/126M	14	G	6.75	3750	110	3970	110	31.93	8.90	651	18.9
245/70R19.5	133/131M	14	G	7.50	4300	110	4540	110	33.03	9.76	629	20.8
245/70R19.5	135/133M	16	H	7.50	4540	120	4805	120	33.03	9.76	629	20.8
285/70R19.5	150/147J	18	J	8.25	6780	130	7390	130	35.24	11.14	590	20.2

SMARTWAY



AFE823

Radial Truck Tire (Regional)

1. Recommended for Regional All Position applications.
2. S-shaped groove bottom reduces stone retention.
3. 5-rib design provides vehicle stability in all weather condition.

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
11R22.5	144/142M	14	G	8.25	5840	105	6175	105	41.50	10.98	501	18.3
11R22.5	146/143M	16	H	8.25	6005	120	6610	120	41.50	10.98	501	18.3
11R24.5	146/143M	14	G	8.25	6005	105	6610	105	43.46	10.98	478	18.3
11R24.5	149/146M	16	H	8.25	6610	120	7160	120	43.46	10.98	478	18.3
285/75R24.5	144/141M	14	G	8.25	5675	110	6175	110	41.34	11.14	503	18.3
285/75R24.5	147/144M	16	H	8.25	6175	120	6780	120	41.34	11.14	503	18.3
295/75R22.5	144/141M	14	G	9.00	5675	110	6175	110	39.92	11.73	520	18.3
295/75R22.5	146/143M	16	H	9.00	6005	120	6610	120	39.92	11.73	520	18.3

Remark : The above technical data are for reference only.

Remark : The above technical data are for reference only.



F816

Radial Truck Tire (Regional)

1. Recommended for Regional All Position applications.
2. Construction optimized for long service life .

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
11R22.5	144/142M	14	G	8.25	5840	105	6175	105	41.50	10.98	501	18.3
11R22.5	146/143M	16	H	8.25	6005	120	6610	120	41.50	10.98	501	18.3
11R24.5	146/143M	14	G	8.25	6005	105	6610	105	43.46	10.98	478	18.3
11R24.5	149/146M	16	H	8.25	6610	120	7160	120	43.46	10.98	478	18.3
285/75R24.5	144/141M	14	G	8.25	5675	110	6175	110	41.34	11.14	503	18.3
285/75R24.5	147/144M	16	H	8.25	6175	120	6780	120	41.34	11.14	503	18.3
295/75R22.5	144/141M	14	G	9.00	5675	110	6175	110	39.92	11.73	520	18.3
295/75R22.5	146/143M	16	H	9.00	6005	120	6610	120	39.92	11.73	520	18.3

SMARTWAY



F816e+

Radial Truck Tire (Regional)

1. Recommended for Regional All Position applications.
2. Optimized for low rolling resistant to save fuel costs.

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
11R22.5	144/142M	14	G	8.25	5840	105	6175	105	41.50	10.98	501	18.3
11R22.5	146/143M	16	H	8.25	6005	120	6610	120	41.50	10.98	501	18.3
11R24.5	146/143M	14	G	8.25	6005	105	6610	105	43.46	10.98	478	18.3
11R24.5	149/146M	16	H	8.25	6610	120	7160	120	43.46	10.98	478	18.3
285/75R24.5	144/141M	14	G	8.25	5675	110	6175	110	41.34	11.14	503	18.3
285/75R24.5	147/144M	16	H	8.25	6175	120	6780	120	41.34	11.14	503	18.3
295/75R22.5	144/141M	14	G	9.00	5675	110	6175	110	39.92	11.73	520	18.3
295/75R22.5	146/143M	16	H	9.00	6005	120	6610	120	39.92	11.73	520	18.3

Remark : The above technical data are for reference only.



SMARTWAY

LLF02e+

Radial Truck Tire (Regional)

1. Designed for on-highway heavy load applications.
2. Wide footprint for even weight distribution.
3. Optimized for low rolling resistant to save fuel costs.

Size	Load Index & Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
315/80R22.5	154/151M	18	J	9.00	7610	120	8270	120	42.36	12.28	490	18.3
315/80R22.5	157/154L	20	L	9.00	8270	130	9090	130	42.36	12.28	490	18.3



T810

Radial Truck Tire (Regional)

1. Recommended for on-highway Long Haul and Regional trailer applications.
2. Rounded shoulder reduces the effects of scrubbing during sharp turns.

Size	Load Index & Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
11R22.5	144/142M	14	G	8.25	5840	105	6175	105	41.34	10.98	503	13.5
11R22.5	146/143M	16	H	8.25	6005	120	6610	120	41.34	10.98	503	13.5
11R24.5	146/143M	14	G	8.25	6005	105	6610	105	43.46	10.98	478	13.5
11R24.5	149/146M	16	H	8.25	6610	120	7160	120	43.46	10.98	478	13.5
255/70R22.5	140/137M	16	H	7.50	5070	120	5510	120	36.61	10.04	567	13.5
285/75R24.5	144/141M	14	G	8.25	5675	110	6175	110	41.34	11.14	503	13.5
285/75R24.5	147/144M	16	H	8.25	6175	120	6780	120	41.34	11.14	503	13.5
295/75R22.5	144/141M	14	G	9.00	5675	110	6175	110	39.92	11.73	520	13.5
295/75R22.5	146/143M	16	H	9.00	6005	120	6610	120	39.92	11.73	520	13.5

Remark : The above technical data are for reference only.

SMARTWAY



T810e+

Radial Truck Tire (Regional)

1. Recommended for on-highway Long Haul and Regional trailer applications.
2. Rounded shoulder reduces the effects of scrubbing during sharp turns.
3. Optimized for low rolling resistant to save fuel costs.

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
11R22.5	144/142M	14	G	8.25	5840	105	6175	105	41.34	10.98	503	12.6
11R22.5	146/143M	16	H	8.25	6005	120	6610	120	41.34	10.98	503	12.6
11R24.5	146/143M	14	G	8.25	6005	105	6610	105	43.46	10.98	478	13.5
11R24.5	149/146M	16	H	8.25	6610	120	7160	120	43.46	10.98	478	13.5
285/75R24.5	144/141M	14	G	8.25	5675	110	6175	110	41.34	11.14	503	13.5
285/75R24.5	147/144M	16	H	8.25	6175	120	6780	120	41.34	11.14	503	13.5
295/75R22.5	144/141M	14	G	9.00	5675	110	6175	110	39.92	11.73	520	12.6
295/75R22.5	146/143M	16	H	9.00	6005	120	6610	120	39.92	11.73	520	12.6



D928

Radial Truck Tire (Regional)

1. Recommended for on-highway Long Haul and Regional drive applications.
2. Open shoulder tread pattern delivers traction in all weather conditions.

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
11R22.5	144/142L	14	G	8.25	5840	105	6175	105	41.69	10.98	498	25.8
11R22.5	146/143L	16	H	8.25	6005	120	6610	120	41.69	10.98	498	25.8
11R24.5	146/143L	14	G	8.25	6005	105	6610	105	43.70	10.98	475	25.8
11R24.5	149/146L	16	H	8.25	6610	120	7160	120	43.70	10.98	475	25.8
285/75R24.5	144/141M	14	G	8.25	5675	110	6175	110	41.57	11.14	500	25.8
285/75R24.5	147/144M	16	H	8.25	6175	120	6780	120	41.57	11.14	500	25.8
295/75R22.5	144/141M	14	G	9.00	5675	110	6175	110	40.16	11.73	517	25.8
295/75R22.5	146/143M	16	H	9.00	6005	120	6610	120	40.16	11.73	517	25.8



LLA18

Radial Truck Tire (Regional)

1. Recommended for Regional applications.
2. Zig-zag groove tread design reduces stone retention.

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
385/65R22.5	158K	18	J	11.75	/	/	9370	120	42.20	15.31	492	20.8
385/65R22.5	160J	20	L	11.75	/	/	9920	130	42.20	15.31	492	20.8



LLA28

Radial Truck Tire (Regional)

1. Recommended for Regional applications.
2. Zig-zag groove tread design reduces stone retention.
3. Tread pattern delivers lateral traction in all weather conditions.

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
425/65R22.5	162K	18	J	12.25	/	/	10500	110	44.25	16.61	469	22.0
425/65R22.5	165J	20	L	12.25	/	/	11400	120	44.25	16.61	469	22.0

Remark : The above technical data are for reference only.

Remark : The above technical data are for reference only.



AAL800

Radial Truck Tire (Regional)

- 1.Suitable for all position axle of trucks running on the multi road.
- 2.Good handling and driving.
- 3.Long life.

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
11R22.5	146/143L	16	H	8.25	6005	120	6610	120	41.50	10.98	501	20.2
12R22.5	150/147L	16	H	9.00	6780	120	7390	120	42.72	11.81	487	20.2
315/80R22.5	156/150L	20	L	9.00	7385	125	8820	125	42.36	12.28	490	20.2



ADL813

Radial Truck Tire (Regional)

- 1.Long life.
- 2.Good grip performance.
- 3.Retreadability.
- 4.Low eccentric wear.

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
11R22.5	146/143L	16	H	8.25	6005	120	6610	120	41.69	10.98	498	25.2
12R22.5	150/147L	16	H	9.00	6780	120	7390	120	42.72	11.81	487	26.5
315/80R22.5	156/150L	20	L	9.00	7385	125	8820	125	42.36	12.28	490	26.5

Remark : The above technical data are for reference only.

Remark : The above technical data are for reference only.

NEW



KMA40

Radial Truck Tire (Mixed Service)

1. Suitable for all position axle of trucks under all kinds of working conditions.
2. Chip cut and abrasion resistance tread compound.
3. Stone rejection design protects groove bottom from stone puncture.
4. Deep tread depth increase mileage and service life.

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
11R22.5	146/143L	16	H	8.25	6005	120	6610	120	41.50	10.98	501	23.1
11R24.5	149/146L	16	H	8.25	6610	120	7160	120	43.46	10.98	478	23.1



AAR919

Radial Truck Tire (Mixed Service)

1. Recommended for Mixed Service All Position application.
2. Pattern provides durability, versatility, and wear.
3. Provides good traction in a variety of conditions.

Size	Load Index & Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
11R22.5	146/143M	16	H	8.25	6005	120	6610	120	41.73	10.98	498	23.9
315/80R22.5	154/151K	18	J	9.00	7610	120	8270	120	42.52	12.40	489	25.2
10.00R20	146/143K	16	H	7.5	6005	120	6610	120	41.50	10.94	501	20.2
10.00R20	149/146K	18	J	7.5	6610	135	7160	135	41.50	10.94	501	20.2

Remark : The above technical data are for reference only.

Mixed Service



LLA08

Radial Truck Tire (Mixed Service)

1. Recommended for Mixed Service applications.
2. Variable angled tread pattern reduces stone retention.
3. Tread pattern delivers lateral traction in all weather conditions.

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
11R22.5	146/143K	16	H	8.25	6005	120	6610	120	41.50	10.98	501	18.9
11R24.5	149/146K	16	H	8.25	6610	120	7160	120	43.46	10.98	478	20.8
12R22.5	152/149K	18	J	9.00	7160	135	7825	135	42.72	11.81	487	21.4
315/80R22.5	157/154K	20	L	9.00	8270	130	9090	130	42.36	12.28	490	22.0
255/70R22.5	140/137M	16	H	7.50	5070	120	5510	120	36.61	10.04	567	16.0



LLA38

Radial Truck Tire (Mixed Service)

1. Recommended for Mixed Service applications.
2. Designed for heavy loads and rough road conditions.
3. Tread pattern delivers traction in all weather conditions.

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
385/65R22.5	160K	20	L	11.75	/	/	9920	130	42.20	15.31	492	20.8
425/65R22.5	165K	20	L	12.25	/	/	11400	120	44.25	16.61	469	22.0
445/65R22.5	168K	20	L	13.00	/	/	12300	120	45.28	17.48	462	22.7

Remark : The above technical data are for reference only.



A968

Radial Truck Tire (Mixed Service)

1. Recommended for Mixed Service applications.
2. Provides good traction in a variety of conditions.
3. Wide footprint for even weight distribution.

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
11R22.5	146/143K	16	H	8.25	6005	120	6610	120	41.50	10.98	501	22.0
11R24.5	149/146K	16	H	8.25	6610	120	7160	120	43.46	10.98	478	22.0



ADR978

Radial Truck Tire (Mixed Service)

1. Recommended for Mixed Service applications.
2. Heavy lugs optimized for cut, tear and puncture resistance.
3. Designed for increased payloads.
4. Excellent traction on rough terrain.

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
13R22.5	156/150K	18	J	9.75	7835	127	8820	127	44.61	12.60	466	26.5



D960

Radial Truck Tire (Mixed Service)

1. Recommended for Mixed Service drive applications.
2. Deep and rigid block design provides traction in all conditions.
3. Designed for increased payloads.

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
265/70R19.5	140/138K	16	H	7.50	5205	112	5510	112	34.13	10.31	609	19.5

Remark : The above technical data are for reference only.



Logging

LEAO TIRE

Coach&Bus



AAU603

Radial Bus Tire (Coach)

1. Recommended for on-highway Long Haul and Regional applications.
2. Construction optimized for long service life.
3. Pattern optimized for stability and ride comfort.

Size	Load Index & Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
11R22.5	146/143M	16	H	8.25	6005	120	6610	120	41.50	10.98	501	20.2
12R22.5	152/149L	18	J	9.00	7160	135	7825	135	42.72	11.81	486	21.4
275/70R22.5	148/145M	16	H	8.25	6395	130	6945	130	37.72	10.87	551	20.2
295/80R22.5	152/149M	18	J	9.00	7160	130	7830	130	41.10	11.73	505	21.4



D950

Radial Truck Tire (Short Haul)

1. Recommended for Short Haul Logging drive applications.
2. Designed for durability and long service life.
3. Provides excellent traction in a variety of conditions and surfaces.

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
11R22.5	146/143K	16	H	8.25	6005	120	6610	120	41.93	10.98	495	29.0
11R24.5	149/146G	16	H	8.25	6610	120	7160	120	43.94	10.98	473	31.4

Remark : The above technical data are for reference only.



AAU802

Radial Bus Tire (Urban)

1. Recommended for on-highway Urban applications
2. Tread design provides good traction in all weather conditions
3. Construction optimized for Urban service useage
4. Wide footprint for long mileage and vehicle stability.

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
11R22.5	146/143F	16	H	8.25	6005	120	6610	120	41.62	10.98	498	24.6
275/70R22.5	148/145J(152/148E)	16	H	8.25	6395	130	6945	130	37.72	10.87	551	24.6
295/80R22.5	152/149J	18	J	9.00	7160	130	7830	130	41.10	11.73	505	25.2
305/70R22.5	152/148J(154/150E)	16	H	9.00	6940	130	7830	130	39.37	12.01	528	25.2

Remark : The above technical data are for reference only.



ADW807

Radial Truck Tire on Ice and Snow (Drive)

- 1.High safety and good handling.
- 2.Optimized rib contact combats uneven wear and improves wet handling and braking.
- 3.Long life.

Size	Load Index& Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
295/80R22.5	152/149K	18	J	9.00	7160	130	7830	130	41.10	11.73	505	25.2
315/80R22.5	154/151K	18	J	9.00	7610	120	8270	120	42.36	12.28	490	25.2
11R22.5	146/143M	16	H	8.25	6005	120	6610	120	41.69	10.98	498	23.9



AFW806

Radial Truck Tire on Ice and Snow (All position)

- 1.High safety and good handling.
- 2.Optimized rib contact combats uneven wear and improves wet handling and braking.
- 3.Low noise.

Size	Load Index & Speed symbols	PR	Load Range	Rim	Max Load and Max Air				Overall Diameter (in)	Section Width (in)	Revolutions per Mile	Tread Depth (32nds)
					Dual		Single					
					lbs	psi	lbs	psi				
11R22.5	146/143M	16	H	8.25	6005	120	6610	120	41.50	10.98	501	18.9
11R24.5	149/146M	16	H	8.25	6610	120	7160	120	43.46	10.98	478	18.9
275/70R22.5	148/145M	16	H	8.25	6395	130	6945	130	37.72	10.87	551	18.9
295/75R22.5	146/143M	16	H	9.00	6005	120	6610	120	39.92	11.73	520	18.9
295/80R22.5	152/149K	18	J	9.00	7160	130	7830	130	41.10	11.73	505	18.9
315/80R22.5	154/151K	18	J	9.00	7610	120	8270	120	42.36	12.28	490	18.9
385/65R22.5	160J	20	L	11.75	/	/	9920	130	42.20	15.31	495	20.8

Remark : The above technical data are for reference only.